

FASCAT[®] Catalysts



About FASCAT® Catalysts

PMC's broad portfolio of high purity tin catalysts is offered in packages ranging from pails to totes. Our outstanding customer service is aligned with global availability and industry-leading technical know-how. FASCAT catalysts are the world's trusted, cost-effective solution for esterification, transesterification and urethane and siloxane cross-linking.

PMC Organometallics is a leading global producer of a broad portfolio of stannous (tin II), monobutyltin, dibutyltin, and dioctyltin catalysts under the FASCAT brand name. Our catalysts are globally recognized for consistent performance. Quality assurance drives our manufacturing processes and provides peace of mind to our customers. As long as proper procedures are followed, FASCAT catalysts will perform consistently, batch after batch, no matter where in the world they are utilized.

Your trusted performer

Electrocoat manufacturers trust FASCAT catalysts for the most exacting specifications for automotive and industrial resin and paste applications.

Your cost-effective solution

Ester manufacturers recognize FASCAT catalysts as superior to caustics and titanates due to overall lower manufacturing costs. Most applications require extremely low loading levels to achieve desired reaction rates.

Your regulatory partner

FASCAT 2000 and 4100 series products are very high purity - offering manufacturers seeking to minimize dibutyltin (DBT) and tributyltin (TBT) confidence when it comes to meeting stringent regulatory standards.

Your global partner

PMC Organometallics has the global production and warehousing capacity to provide the FASCAT product you need when you need it. Visit FASCAT.com to see our list of global distributors.

Your formulating aide

FASCAT catalysts provide manufacturers of urethanes and siloxanes a cost-effective means of enhancing or varying cure speed and pot life.

pmc organometallics™



FASCAT® Applications

FASCAT catalysts are effective for a wide variety of end-use applications. Many FASCAT catalysts behave as Lewis acids, making a wide range of synthetic chemistry possible. Listed below are typical uses.



FASCAT® catalysts are used in the production of:

Adhesives and Sealants

Adhesives and sealants rely on FASCAT catalysts to enhance curing properties. Both polyurethane and silicone-based chemistries are common applications in both 2K and 1K systems.

Biofuels and Synthetic Lubricants

Manufacturers seeking high yield and minimal side reactions use FASCAT catalysts to esterify the monomeric esters used for biofuels and synthetic lubricants. Solid and liquid catalysts are available and can be distilled or filtered from the finished products.

Coatings

FASCAT catalysts are widely used in coatings applications, both for making resins and enhancing the cure of the final formulation. Food contact (FDA) grade catalysts are also available.

A specialized FASCAT solution exists for manufacturers working with a variety of resins and coatings:

- Polyester resins
- Alkyd resins
- Polyurethanes
- Epoxy resins
- Hybrids: polysiloxane/epoxy hybrids
- Electrophoretic coatings (e-coat)

Elastomers

FASCAT catalysts can be used to vary the speed of cross-linking for polyurethanes (PUR, TPU, TPE) and for silicones (SI, Q, VMQ). Other synthetic rubber compounds also benefit from FASCAT technology.

Foams

From mattresses to insulation, polyurethane foams are made from reacting polyether polyols or polyester polyols with isocyanate in the presence of a FASCAT catalyst and tertiary amine. PMC manufactures two primary products for foam production. Contact our experts for special selectivity or VOC requirements.

Plasticizers

FASCAT catalysts are used to manufacture phthalate esters, in particular dioctyl phthalate (DIOP) esters. These high molecular weight phthalate esters are used as plasticizers in a wide variety of end uses from enteric coatings of pharmaceuticals, to viscosity control agents, film formers, suspending agents, personal-care products, and soft plastics.

Unsaturated Polyester Resins

FASCAT catalysts are used to manufacture polyester resins that are used to manufacture composites.

Use our product selector tool at www.FASCAT.com to find out which FASCAT catalysts best meet your needs.

FASCAT® Product Portfolio

Highly selective catalysts for esters, urethanes, and siloxanes

Product	CAS #	Chemical Name(s)	Product Description	Chemical Structure
FASCAT 2001 ●	814-94-8	Stannous oxalate	<ul style="list-style-type: none"> White to off-white solid powder Production of monomeric and polymeric plasticizers, fatty acid esters, and synthetic lubricants Removable from final ester by filtration 	
FASCAT 2003 ●	301-10-0	Stannous bis (2-ethylhexanoate) <i>also known as</i> Stannous octoate	<ul style="list-style-type: none"> Pale yellow liquid Production of oleochemicals and silanol condensation reactions Urethane cross-linking Urethane foam gelling 	
FASCAT 2004 ●	7772-99-8	Stannous dichloride	<ul style="list-style-type: none"> Solid white to off-white flaked material Esterification catalysts Removable from final ester by filtration Used in tin plating and other metal finishing 	$\text{Cl}-\text{Sn}-\text{Cl}$
FASCAT 4100 ●	2273-43-0	Monobutyltin oxide <i>also known as</i> Butyl stannic acid	<ul style="list-style-type: none"> Amorphous white solid for transesterification and esterification Hydrolytically stable Versatile, neutral catalyst Extremely pure with low levels of DBT and TBT contamination 	
FASCAT 4101 ●	13355-96-9	Monobutyltin dihydroxychloride	<ul style="list-style-type: none"> Amorphous white solid for transesterification and esterification Hydrolytically stable Soluble in several solvents, NaOH, HNO3 Extremely pure with low levels of DBT and TBT contamination 	
FASCAT 4102 ●	23850-94-4	Monobutyltin tris (2-ethylhexanoate)	<ul style="list-style-type: none"> Pale yellow liquid Esterifications of aromatic polyester polyols Ring opening polymerization Plasticizers, including dioctyl phthalate 	
FASCAT 4200 ●	1067-33-0	Dibutyltin diacetate	<ul style="list-style-type: none"> Clear, colorless to pale yellow liquid Silanol condensation reactions for caulk and sealant applications Production of blocked isocyanates Cross-link urethane coating systems Transesterifications 	
FASCAT 4201 ●	818-08-6	Dibutyltin oxide	<ul style="list-style-type: none"> Amorphous white solid Transesterification catalyst for methacrylate esters High temperature transesterification reactions for coating resins Cross-linking electrocoat resins and pastes Finely ground available - FASCAT 4203 	
FASCAT 4202 ●	77-58-7	Dibutyltin dilaurate	<ul style="list-style-type: none"> Yellow amber, oily liquid Cross-link two-component urethane coating systems Cross-link RTV silicone systems Cross-link polyethylene/silane (PEX) co-polymer systems Gelling catalyst of flexible and rigid polyurethane foams 	
FASCAT 4208X ●	2781-10-4	Dibutyltin bis (2-ethylhexanoate) in xylene (50 wt%)	<ul style="list-style-type: none"> White to straw liquid Silanol/silicone condensation reactions 	
FASCAT 4210 ●	63-18-1	Dibutyltin dichloride	<ul style="list-style-type: none"> White crystalline solid Intermediate for producing dibutyltin compounds Precursor for glass coating Reactive additive for synthetic rubber to improve carbon black dispersibility 	

FASCAT catalysts can have a 1 or 2 year shelf life as indicated at room temperature in an unopened container. Shelf life is determined based on manufacture date or recertification date as indicated on the certificate of analysis (CoA).

Product	CAS #	Chemical Name(s)	Product Description	Chemical Structure
FASCAT 4224 ●	68298-38-4	Dibutyltin bis (1-thioglyceride)	<ul style="list-style-type: none"> • Clear to light colored liquid • Highly selective for polyurethane systems. • Hydrolytic stability for waterborne coatings and adhesives • Formulations needing long pot life at room temperature, quick cure at elevated temperatures 	
FASCAT 4233 ●	Proprietary	Butyltin mercaptide	<ul style="list-style-type: none"> • Light amber oily liquid • Synthesis and curing of polyurethanes • Delayed action cure compared to organotin carboxylates 	Proprietary
FASCAT 4350 ●	Proprietary	Butyltin oxide	<ul style="list-style-type: none"> • Amorphous white powder • Alkyd resins --> alcoholysis and esterification steps • 20% to 25% reduction in reaction time as well as improved color and haze compared to lithium catalyzed systems 	Proprietary
FASCAT 4351 ●	76-87-9	Triphenyltin hydroxide	<ul style="list-style-type: none"> • White powder • Commonly used in fungicides • Acid-epoxy reactions 	
FASCAT 4400 ●	7646-78-8	Tin tetrachloride <i>also known as</i> Stannic chloride	<ul style="list-style-type: none"> • Clear to yellow, fuming liquid • Chloromethylation and reaction of epichlorohydrin with alcohols to form glycidyl ethers • Organic synthesis 	
FASCAT 8201 ●	870-08-6	Diocetyl tin oxide	<ul style="list-style-type: none"> • Amorphous white solid • Transesterifications • Cross-linking electrocoat resins and pastes • Slightly less reactive than DBTO, but fewer regulatory restrictions • Finely ground available - FASCAT 8203 	
FASCAT 8202 ●	3648-18-8	Diocetyl tin dilaurate	<ul style="list-style-type: none"> • Yellow amber, oily liquid • A versatile catalyst used in various urethan cross-linking reactions and silanol condensation reactions 	
FASCAT 9100 ●	2273-43-0	Monobutyltin oxide <i>also known as</i> Butyl stannic acid (Food Grade)	<ul style="list-style-type: none"> • FDA grade of FASCAT 4100 that satisfies 21 CFR 175.300, 21 CFR 177.2420, and 21 CFR 175.105. 	
FASCAT 9102 ●	23850-94-4	Monobutyltin tris (2-ethylhexanoate) (Food Grade)	<ul style="list-style-type: none"> • FDA grade version of FASCAT 4102 used in cross-linked polyester resins for food contact articles intended for repeated use under 21 CFR Sec. 177.2420(b)3. • The maximum amount of catalyst cannot exceed 0.2 percent of the polyester resin under 21 CFR Sec. 175.300. 	
FASCAT 9201 ●	818-08-6	Dibutyltin oxide (Food Grade)	<ul style="list-style-type: none"> • FASCAT 9201 is the food grade version of FASCAT 4201 that satisfies 21 CFR 175.300, 21 CFR 177.2420, and 21 CFR 175.105. 	

Full Descriptions and Technical Data Sheets Are Available at
www.FASCAT.com

Product Stewardship for FASCAT® Catalysts

PMC will help you navigate the facts and regulations for organotin products



Tin (Sn) in its elemental form, CAS 7440-31-5, has a silvery or gray appearance. Tin is commonly extracted from the mineral cassiterite, and is nontoxic.

Uses of tin go back 3000 years when it was commonly mixed with copper to make bronze, which remains a widely used alloy today. When tin is used to form organometallic complexes, a wide range of toxicities can be observed. Some species are toxic while others have low toxicities.

General Toxicity Rules

$R = \text{Me} > \text{Bu} > \text{Oct}$

$R_3\text{SnX} > R_2\text{SnX}_2 > R\text{SnX}_3$

R = Organic group (Methyl, Butyl, Octyl)
X = Ligand (Halide, Oxide, Mercaptide, etc.)

What do you need to know regarding the use of FASCAT tin catalysts?

FASCAT catalysts are not Substances of Very High Concern (SVHC). Although FASCAT 4200 and 8200 series catalysts have REACH¹ restrictions, they are generally effective at catalyzing reactions at levels below the 0.1% REACH threshold equivalent weight of tin.

Navigating the regulatory environment around the world can be tough – let our experts help guide you!

How does REACH* specifically impact organotins?

Organotin compounds cannot be used as biocides in free association paint, as antifouling agents for submerged items, or for industrial water treatment.

Tri-substituted organostannic compounds, such as tributyltin (TBT) compounds and triphenyltin (TPT), and dibutyltin (DBT) compounds are limited to 0.1% by weight of tin in consumer products.

Similarly, dioctyltin (DOT) compounds are limited to 0.1% by weight of tin in articles that would come in contact with the skin (gloves, footwear, nappies, floor coverings etc.).

Other REACH registered tin compounds are not restricted.

For additional information regarding our FASCAT product stewardship,

ask our experts at www.FASCAT.com/ask-the-expert/ or email us at regulatory@fascat.com

¹ Regulation, Evaluation, Authorization & Restriction of Chemicals

* Per REGULATION (EC) No 1907/2006 and COMMISSION REGULATION (EU) No 276/2010

FASCAT® Catalysts Help to Provide Renewable Energy

With applications in the wind turbine industry, FASCAT catalysts assist in the creation of environmentally-friendly energy solutions.

FASCAT 2000 & 4000 Series

Used for esterification of synthetic lubricants for mechanical systems

FASCAT 4100 & 4200 Series

Used in unsaturated polyester resin production for composites, gelcoat resin production, and for urethane topcoat curing

FASCAT 4100 & 4200 Series

Used for coatings resin production and urethane topcoat curing

pmc  **organometallics™**

For more information on our FASCAT® catalysts and their applications,

Visit our website at www.FASCAT.com



- ★ Headquarters
- Manufacturing Locations

About PMC Group



PMC Group is a growth oriented, diversified, global chemicals company dedicated to innovative solutions to everyday needs in a broad range of end markets including plastics, consumer products, electronics, paints, packaging, personal care, food, automotive and pharmaceuticals. The Company was built on a sustainable model of growth through innovation while promoting social good. Dedicated to sustainability, PMC operates from a global manufacturing, innovation and marketing platform with facilities and personnel in the Americas, Europe and Asia.

Today, through a combination of innovative organic growth coupled with strategic acquisitions, PMC has become a global organization with manufacturing, research and marketing organizations throughout the world all fueled by continuous innovation and a dedication to unassailable quality, service and safety of our people and the environment.

pmc organometallix™

www.FASCAT.com

PMC Organometallix
2316 Highland Ave
Carrollton, KY 41008
USA
+1 855 638 2549 or +1 856 638 2157
www.pmcorganometallix.com

PMC Beijing Chemical Co., Ltd.
No. 1, Wutong Road
Tongzhou Industrial Development Zone
Tongzhou District, 101113 Beijing
CHINA
+86 10 6156 4749 ext. 804

Any product information or other information published in this brochure is given to the best of PMC Organometallix, Inc.'s knowledge. All information shall not, however, as far as legally permissible, create any guarantee or representation of any kind or any liability of PMC Organometallix, Inc. and shall not relieve the User from undertaking its own investigations and tests.

FASCAT® is a trademark of PMC Group, Inc. and its subsidiaries.
COPYRIGHT © MAY 2018 PMC GROUP, INC. ALL RIGHTS RESERVED.

OMX-001